

**Description & Features:**

- Unique pressure instrument utilizing colour coded cases for easy identification of processes
- 4 different colours that are UV resistant and will not fade
- Stainless steel or brass internals, liquid fillable
- CRN registered
- 5 year warranty

Applications:

- Used for easy identification of process or pressure
- Well suited for use where heavy vibration or pulsation exist
- Used on machinery, process lines, compressors, hydraulics

Specifications	Stainless Steel Internals	Brass Internals
Dial	4" (100mm) white aluminum with black and red markings	4" (100mm) white aluminum with black and red markings
Case	PBT Polyethylene terephthalate - colour coded	PBT Polyethylene terephthalate - colour coded
Lens	Polycarbonate	Polycarbonate
Ring	PBT Polyethylene terephthalate - colour coded	PBT Polyethylene terephthalate - colour coded
Socket	316L SS	OT 58 brass
Connection	1/4" NPT or 1/2" NPT standard	1/4" NPT or 1/2" NPT standard
Bourdon Tube	316L SS, drawn seamless	Phosphor bronze
Movement	304 SS	Gears are OT 59 brass, plates are AISI 304 SS
Pointer	Aluminum, anodized black	Aluminum, anodized black
Welding	TIG, silver alloy	Tin/copper alloy for pressures below 600 psi (4,147 kPa). Silver alloy for pressures 600 psi (4,147 kPa) and above
Over-Pressure Limit	30% for pressures up to 600 psi (4,147 kPa) 15% for pressures over 600 psi (4,147 kPa)	25% for pressures up to 1,400 psi (9,653 kPa) 15% for pressures over 1,400 psi (9,653 kPa)
Gasket Material	EPDM	Silicone rubber for socket, EPDM for lens, filling plug and blow-out vent
Working Pressure	Maximum 75% of full scale value	Maximum 75% of full scale value
Ambient/Process Temperature	-40°F to 150°F (-40°C to 65°C) dry	-40°F to 150°F (-40°C to 65°C) dry
Accuracy	±1% ANSI/ASME Grade 1A	±1% ANSI/ASME Grade 1A
Enclosure Rating	IP65 per UEC 529, UNI 8896	IP65 per UEC 529, UNI 8896

Order Codes (products in bold are normally in stock)

Dial Size	4" (100mm)			
Connection Bottom	1/4"	1/2"	3/4"	1"
Movement, Socket, Tube	Brass	Brass	SS	SS
30" Hg. vacuum/kPa	PCC600C	-	PCC640C	PCC655C
30"/0/15 psi/kPa	PCC1020C	-	PCC1036C	PCC1044C
30"/0/30 psi/kPa	PCC1021C	-	PCC1037C	PCC1045C
30"/0/60 psi/kPa	PCC1022C	-	PCC1038C	PCC1046C
30"/0/100 psi/kPa	PCC1023C	-	PCC1039C	PCC1047C
30"/0/160 psi/kPa	PCC1024C	-	PCC1040C	PCC1048C
30"/0/200 psi/kPa	PCC1026C	-	PCC1042C	PCC1050C
30"/0/300 psi/kPa	PCC1027C	-	PCC1043C	PCC1051C
0 - 15 psi/kPa	PCC601C	-	PCC641C	PCC656C
0 - 30 psi/kPa	PCC602C	-	PCC642C	PCC657C
0 - 60 psi/kPa	PCC603C	-	PCC643C	PCC658C
0 - 100 psi/kPa	PCC604C	-	PCC644C	PCC659C
0 - 160 psi/kPa	PCC605C	-	PCC645C	PCC660C
0 - 200 psi/kPa	PCC606C	-	PCC646C	PCC661C
0 - 300 psi/kPa	PCC607C	-	PCC647C	PCC662C
0 - 400 psi/kPa	PCC610C	-	PCC650C	PCC666C
0 - 600 psi/kPa	PCC608C	-	PCC648C	PCC663C
0 - 1,000 psi/kPa	PCC609C	PCC624C	PCC649C	PCC664C
0 - 1,500 psi/kPa	-	PCC625C	-	PCC665C
0 - 2,000 psi/kPa	-	PCC626C	-	PCC667C
0 - 3,000 psi/kPa	-	PCC627C	-	PCC668C
0 - 5,000 psi/kPa	-	PCC628C	-	PCC669C
0 - 10,000 psi/kPa	-	PCC629C	-	PCC670C
0 - 15,000 psi/kPa	-	PCC630C	-	PCC671C
0 - 20,000 psi/kPa	-	PCC639C	-	PCC672C

Other ranges and connection sizes available upon request. For scale change, refer to How to Order Guide for scale codes. **For options, attach suffix to end of order code: i.e. PCC603C-G for GLYCERIN FILL.**

Colour Coded Cases	Colour	Dial 4" (100mm)
	Red	1Y
	Yellow	2Y
	Black	3Y
	Blue	5Y

Add appropriate colour code as suffix.
(e.g. PCC662C1Y = Gauge Order Code + Case Colour Code)

Option suffix:

G = Glycerin filled case
SG-4 = 4" safety glass

4" Bottom Connection

